EF 107 OX *XSafe*

Ice maker with built-in bin, up to 130 kg



CHARACTERISTICS

• It produces granular ice flakes with a hardness of 75%.
• Ice scoop holder securely positioned in the ice bin.
• Computerized Advanced Diagnostic Testing.
• Inlet and outlet airflow on the front panel (air-cooled model only) for built-in installation.
• Front-access condenser air filter, removable and washable (air-cooled version only).
• Easy access to the front panel of the machine's technical/service area.
• PWD - Progressive Water Drainage: Pumps excess residual water up to a distance of 15 meters.
• XSafe: All-natural, machine-integrated sanitizing system. It acts automatically and continuously keeping the machine clean and sanitized.



EF Flake
FLAKE
-

Model	Cubetto	Ø	H	Weight
EF Flake				

CONDENSATION SYSTEM

Air
Water

REFRIGERANT GAS

R290

VOLTAGE V/HZ/PH

230\50\1
220-240\60\1

BIN CAPACITY

KG
30

CERTIFICATIONS

OPERATIONAL REQUIREMENTS

	Minimum	Maximum
Air temperature	10	43
Water temperature	5	38
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Voltage	-10%	+10%

IMPORTANT NOTE
Models and specifications are subject to change without notice. This spec sheet is for sales purposes only. For technical documentation, please refer to our service manuals.

www.scotsman-ice.it

EF 107 OX *XSafe*

Scotsman Ice Systems

Ice maker with built-in bin, up to 130 kg



MACHINE DATA	SHIPPING DATA	
Dimensions (LxWxH): 592 x 622 x 1078 mm Net weight 67 kg	Dimensions (LxWxH): 67 x 69 x 116 cm Net weight 74 kg	(*) The data refers to the following temperature conditions: 32°C Ambient / 21°C Water

			Ice production kg in 24 h °C Ambient / °C Water			Heat dispersion	Consumo Energia (*)	Consumption Water (*)	Instant power	Cables	Fuse
Version	Voltage	Condensation	10°C/10°C	21°C/10°C	32°C/21°C	kW	kWh/24h	l/h	W	No. x Ømm²	A
EF 107 WS EASY	230\50\1	W	122	115	102	0,00	9,0	35,0	340	1,50	10
EF 107 AS EASY	220-240\60\1	A	147	138	108	0,90	11,0	5,0	484	1,50	10