





Aroma Perfect Taste




Model: CSASG1VA



SEASONER CABINET - CURED MEAT - SERIE AROMA - TEMP. -2/ +30 °C - 510 LT. GLASS DOOR - AIR CONDENSING UNIT



Always perfect results



Ideal climate




Easy to use



Experience at your service




Maximum visibility




Flexibility




Energy saving



Ideal for any installation



Create your layout



Easy to clean



**COMMANDS, CONTROLS AND SAFETY DEVICES**

- HACCP alarm management.
- Specific probe for humidity regulation.
- Connectivity with Wi-Fi remote control (optional).
- 5" touch screen color display with control interface
- Responsive humidity management
- Automatic climate change management
- The know-how of the best experts at your disposal

**STRUCTURAL CHARACTERISTICS**

- Monoblock construction.
- Internal stainless steel.
- External in Skinplate steel.
- 80 mm-thick insulation.
- High density CFC and HCFC-free PU insulation (42 kg/m3).
- Ergonomic handle with wooden insert.
- Self-closing doors with opening position block at 100° and magnetic gaskets on all 4 sides.
- Silk-screened tempered glass easily-open Dashboard to facilitate periodic maintenance (condenser cleaning).
- Rounded cell corners for easy cleaning.
- Lower infill plinth.
- Indirect ventilation thanks to the full-length duct system for optimal air circulation and uniform temperature distribution.
- 4000K LED door lighting.
- Locking fixtures.
- Wide range of customization possibilities
- Double glazed door with high insulation level

**REFRIGERANT GROUP**

- Monoblock ceiling system with an evaporator outside the cold room to allow for the exploitation of the entire refrigerated volume.
- Automatic defrost and defrost water self evaporating without the use of energy.
- Tropicalized group (class "T" 43°C).
- High efficiency tropicalized refrigeration unit.
- Climate class 4.

**STANDARD EQUIPMENT**

WI-FI: WI-FI CONNECTION  
ZCTP: CLOSING PLINTH  
2-CGC: N. 2 C SLIDES COUPLE  
GAC: HOOK  
VRG: DIP TRAY

**OPTIONAL TO BE REQUESTED WHEN ORDERING**

TS-AVPG: AC 208/230 V - 60 HZ

**EXTRA ACCESSORIES THAT CAN BE INSTALLED FOLLOWING PURCHASE**

IOTC-3: COLDCLOUD CONNECTION FEE - 3 YEARS  
IOTC-1: COLDCLOUD CONNECTION FEE - 1 YEAR  
KRT-AVPG: WHEEL KIT WITH BRAKE  
VRG: DIP TRAY  
IOTK-A: CONNECTIVITY KIT  
CGCA-A: PAIR OF "C" SHAPED GUIDES WITH ANTI-TIP  
GAC: HOOK

**DIMENSIONS**

Width	mm	780
Depth	mm	965
Height	mm	2090
Door Span Width	mm	620
Internal Depth	mm	725
Door Span Height	mm	1442
Package width	mm	820
Package depth	mm	1005
Package height	mm	2240
Package volume	m <sup>3</sup>	1,85
Weight	Kg	205
Weight with package	Kg	215

**TECHNICAL DATA**

Working temperature	°C	-2/+30
Motor		Air condensing unit
Climate class		Classe 4
GWP - Global Warming Potential		1430
Refrigerant - Type		R134A
Refrigerant - Quantity	g	380


**CAPACITY**

Capacity		510 Lt
----------	--	--------

**POWER SUPPLY**

Power supply voltage	V	230
Max electric power	kW	1715
Cooling power	W	320
Max consumption	A	8,3
Frequency	Hz	50

\* TN - Evap. temp. -10°C / Cond. temp. +45°C || BT - Evap. temp. -25°C / Cond. temp. +45°C.



DIMENSIONI mm  
DIMENSIONS [in]

A = 140 / 200 PIEDINI - FEET  
A = 155 RUOTE  $\varnothing$  100 - CASTORS  $\varnothing$  100

- E** IT - INGRESSO CAVO ALIMENTAZIONE ELETTRICA  
EN - ELECTRICAL POWER SUPPLY CABLE INLET  
FR - ENTRÉE DU CÂBLE D'ALIMENTATION ÉLECTRIQUE  
DE - ANSCHLUß STROMKABEL  
ES - ENTRADA CABLE DE ALIMENTACIÓN ELÉCTRICA  
RU - ВХОД ДЛЯ ЭЛЕКТРИЧЕСКОГО КАБЕЛЯ ПИТАНИЯ

- H3** CONNESSIONE INGRESSO ACQUA UMIDIFICATORE  
HUMIDIFIER WATER INLET CONNECTION