MXF 327 OX XSafe

Modular machines up to 133 kg

Scotsman Ice Systems



CHARACTERISTICS

• Materials: AISI 304 stainless steel and a new removable grate
• Core Ice System: stable evaporation system (axial load).
• New main evaporator: highly balanced screw (dual-profile system).
• New gearmotor: improved evaporator stability and no noise.
• Innovative ice crusher: very dry ice—12% water content.
• Simplified cleaning process and standard XSafe (automatic sanitization system).
• New high-tech water tray with an easy-to-adjust system.
• New ice level sensor: for uninterrupted operation.
• New display: touchscreen and smart. XWave: New app with improved electronics and programming.



MXF SUPER FLAKE
SUPER FLAKE
-

Model	Cubetto	Ø	H	Weight
MXF SUPER FLAKE				

CONDENSATION SYSTEM

Air
Water

REFRIGERANT GAS

R290

VOLTAGE V/HZ/PH

230\50\1
220-240\60\1

RECOMMENDED CONTAINERS

Bin	Compatibility
NB 193	√
SB 193	√
SB 322	√
NB 393	SCBINTOPMXFSB30
SB 393	SCBINTOPMXFSB30
SB 530	SCBINTOPMXFSB30
SB 550	SCBINTOPMXFSB42
SIS 300	•

LEGEND
√ : Perfect combination of machine and container
• : Ice drop hole to be cut at installation
CBTxxxxxxxxxx : Additional accessory required

CERTIFICATIONS

OPERATIONAL REQUIREMENTS

	Minimum	Maximum
Air temperature	10	43
Water temperature	5	38
Water pressure	1 bar (14 psi)	5 bar (70 psi)
Voltage	-10%	+10%

IMPORTANT NOTE
Models and specifications are subject to change without notice. This spec sheet is for sales purposes only. For technical documentation, please refer to our service manuals.

www.scotsman-ice.it

MXF 327 OX *XSafe*

Scotsman Ice Systems

Modular machines up to 133 kg



MACHINE DATA	SHIPPING DATA	
Dimensions (LxWxH): 560 x 615 x 450 mm Net weight 44 kg	Dimensions (LxWxH): 63 x 69 x 63 cm Net weight 54 kg	(*) The data refers to the following temperature conditions: 32°C Ambient / 21°C Water

			Ice production kg in 24 h °C Ambient / °C Water			Heat dispersion	Consumo Energia (*)	Consumption Water (*)	Instant power	Cables	Fuse
Version	Voltage	Condensation	10°C/10°C	21°C/10°C	32°C/21°C	kW	kWh/24h	l/h	W	No. x Ømm²	A
MXF 327 AS 230/50/1	230\50\1	A	133	123	90	1,00	11,0	4,0	477	1,50	10
MXF 327 WS 230/50/1	230\50\1	W	125	120	100	1,00	10,0	43,0	430	1,50	10
MXF 327 AS 230/60/1	220-240\60\1	A	133	122	105	1,10	12,0	4,0	580	1,50	10