

## 2 Solid Door Upright Fridge

Series: ReFlex

Dimensions: 1220 mm (W) × 760 mm (D) × 1985 mm (H)

Project: \_\_\_\_\_

Item #: \_\_\_\_\_



A two solid door upright fridge designed to store food at safe temperatures in busy kitchens at venues such as restaurants, clubs, pubs, and cafés. It is engineered to safely store food, and is energy-tested at climate class 5 to operate in ambient environments of up to 40°C. Certified M1 performance means guaranteed food storage between 1°C and 4°C, which is further adjustable via the SKOPE-connect smartphone app from -2°C to 15°C. The entire cabinet is made from 304 AISI stainless steel through the interior and exterior, over an insulating cyclopentane foamed core. With a 1985 mm height (including castors), 1220 mm width and 760 mm depth, it is suitable for food storage in back-of-house applications. The two self-closing solid swing doors are fitted with built-in key locks. Inside the fridge, there is a door-activated LED light and 5 × height-adjustable plastic-coated wire shelves per door. The top-mounted fully removable refrigeration cartridge uses R290 natural refrigerant for low energy consumption, low heat discharge and low noise output. It can be easily removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to the free SKOPE-connect app to enable you to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all regional refrigeration and electrical safety standards.



Warranty




304 Stainless Steel



Natural Refrigerant



SKOPE-connect



### Cabinet

<b>Range</b>	ReFlex		
<b>Finish</b>	Stainless steel 304 AISI		
<b>Insulation</b>	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso pentane (C5H10/C5H12)	
	Type	Solid swing door (Barrel lock)	
<b>Doors</b>	Opening Size	Height (mm)	1375
		Width (mm)	495
<b>Shelving</b>	Ten adjustable height plastic coated wire shelves		
	Adjustable height shelves: 530mm wide x 530mm deep		
<b>Lighting*</b>	2 x 1200mm, 12W LED		

### Dimensions†

	External	Internal	Packed
<b>Width (mm)</b>	1220	1100	1270
<b>Depth (mm)</b>	760	600	810
<b>Height (mm)</b>	1985 (castors)	1395	2000
<b>Weight (kg)</b>	159		174
<b>Gross Volume (L)</b>	921		
<b>Net Volume (L)</b>	712		
<b>Footprint (m<sup>2</sup>)</b>	0.93		

### Ventilation (mm)

Top	300	Sides	0	Rear	0
-----	-----	-------	---	------	---

### Product Loading

Facing	330 ml can	80	660 ml bottle	70
<b>Loading</b>	330 ml can	640	600 ml bottle	490

### Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm		±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm		-5 mm to +10 mm	+15 mm

### Performance

<b>Product Temperature Range (°C)</b>	1°C to 4°C (adjustable* from -2°C to 15°C)		
<b>Maximum Ambient Temperature (°C)</b>	40		
<b>Sound Power Level (dB(A))</b>	Standard	64.3	
	Hush Mode*	62.1	

### Energy Rating Standards

<b>Energy Efficiency Class</b>	E		
<b>Energy Efficiency Index</b>	80.25		
<b>Climate and Temperature Class</b>	5M1		
<b>Total Energy Consumption</b>	3.91 kWh/24 h		
<b>Annual Energy Consumption</b>	1427 kWh		

### Electrical

<b>Supply</b>	220-240 volts a.c., 50 Hz, Single phase supply		
<b>Cord</b>	2000 mm power cord with 3-Pin, 10 amp, G-Type plug		
<b>Current draw (A)</b>	2.0		

### Refrigeration

<b>Controller</b>	SCS Connect		
<b>System Type</b>	Removable cartridge		
<b>Cartridge Weight (kg)</b>	22		
<b>Refrigerant/Charge</b>	R290/90 g		
<b>Nominal Capacity (W)</b>	650		
<b>Heat Rejection (W)</b>	Average	165	Peak 205
<b>Defrost Type</b>	Automatic, electric		
<b>Drainage</b>	No plumbing required		

\* Accessible via the free SKOPE-connect™ app.



RF7.UPR.2.SD  
on the SKOPE website