

Two Glass Door Top Mount Upright Fridge

Series: ActiveCore

Dimensions: 1130 mm (W) × 745 mm (D) × 2200 mm (H)

Project: _____

Item #: _____



A high-efficiency, top-mounted, heavy duty, 2-door display fridge suitable for front and back-of-house applications including restaurants, cafés, clubs, pubs, bars, quick service restaurants, and more. Made from powder-coated, galvanised steel, the cabinet comes complete with five plastic-coated wire shelves, easily adjustable via SKOPE's unique ezi-clip and numbered shelf supports. The "frameless" glass doors provide maximum product viewing and are designed for condensation protection via the double-glazed, argon-filled, low-e, insulated panels. The high impact built-in LED lights can be timed to turn on and off according to your opening times via the free SKOPE-connect smartphone app. A non-illuminated sign panel is included, with space to display your own branding. With M1 compliance, the fridge is engineered to store food and drinks at a standard 1°C to 4°C (adjustable up to 15°C). This high-performance model is the most energy efficient on the market, and is certified to climate class 3. It is fully tested to operate in ambient environments of up to 40°C (climate class 5). The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge, and low noise output. The top-mounted, fully removable, modular refrigeration cartridge can be easily removed in line with best practice for safe servicing of flammable refrigerants. With the same cartridge being used in both top and bottom-mounted fridges from 600 L to 1000 L, you achieve the fastest possible servicing times with minimal business disruption. The fridge includes a smart controller that connects to the free SKOPE-connect app, enabling you to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all regional refrigeration and electrical safety standards.



Warranty




ActiveCore Technology



Natural Refrigerant



SKOPE-connect



Cabinet

Range	TME		
Finish	Powdercoat galvanised steel		
Insulation	Type	PU foam	
	Thickness (mm)	50	
	Blowing Agent	Cyclo-iso Pentane (C5H10/C5H12)	
Doors	Type	Glass swing door (double-glazed, single Low-E, argon-filled), Tab-locking	
	Height (mm)	1570	
	Opening Size	Width (mm)	436
Shelving	Five adjustable height plastic-coated wire shelves Wire shelves adjustable height: 1015mm wide x 470mm deep		
Lighting*	2 x 1400 mm, 15 W LED		

Dimensions†

	External	Internal	Packed
Width (mm)	1130	1030	1200
Depth (mm)	745	555	760
Height (mm)	2200 (castors)	1570	2220
Weight (kg)	201		225
Gross Volume (L)	897		
Net Volume (L)	n.a.		
Footprint (m²)	0.84		

Ventilation (mm)

Top	300	Sides	0	Rear	0
-----	-----	-------	---	------	---

Product Loading

Loading	330 ml can	525	660 ml bottle	420
---------	------------	-----	---------------	-----

Dimensional Tolerances

† Allow for dimensional tolerances when installing the cabinet(s).

Linear dimensions	Single cabinet		Multiple cabinets	
			At each joint	At each end wall
Less than 1 metre	±5 mm		±5 mm	+15 mm
More than 1 metre	-5 mm to +10 mm		-5 mm to +10 mm	+15 mm

Performance

Product Temperature Range (°C)	1°C to 4°C (adjustable* from 1°C to 15°C)
Maximum Ambient Temperature (°C)	40
Sound Power Level (dB(A))	60.2

Energy Rating Standards

Energy Efficiency Class	B
Energy Efficiency Index	11.26
Climate and Temperature Class	3M1
Total Energy Consumption	2.93 kWh/24 h
Annual Energy Consumption	1,071.00 kWh

Electrical

Supply	220-240 volts a.c., 50 Hz, Single phase supply
Cord	2,000 mm power cord with 3-Pin, 10 amp G Type plug
Current draw (A)	1.7

Refrigeration

Controller	SCS Connect		
System Type	Removable cartridge		
Cartridge Weight (kg)	27		
Refrigerant/Charge	R290/111 g		
Nominal Capacity (W)	547		
Heat Rejection (W)	Average	130	Peak 215
Defrost Type	Automatic, off-cycle		
Drainage	No plumbing required		



TME1000N-A
on the SKOPE website

* Accessible via the free SKOPE-connect™ app.